

# TETRA *display 40"*<sup>®</sup>

Ruggedised 40" Display

- 40" TFT Color Display
- 15:9 WXGA
- WXGA resolution
- Contrast 200:1.
- Luminance 450cd/m<sup>2</sup>
- Ruggedised cabinet
- Operating between -10 °C to +50 °C
- Certified IP54 & MIL STD 810F



## TETRA *display 40"*<sup>®</sup>

The Tetra display 40" allows an optimal use of modern command control communication and information systems, even under hardest environmental conditions .

# TETRA *display 40"*®

## ■ Display

40" TFT color display  
15:9 WXGA  
XXGA resolution  
Depiction of about 16,7 M colors  
Viewing angle vertical and horizontal 170°  
Contrast 200:1  
Luminance 450cd/m<sup>2</sup>  
CCLF Type 1 20.00 hours LVDS  
Prisma analog Controller Board  
LVDS/VGA  
The display adjustment, OSD-Menu, is accessible by the foil keyboard from the front.

### Optional : Shockmount

Stand Unit for Table Use  
Stand Unit for Free-Standing Operating  
Suspension Systems for Cabin  
Transport Boxes  
DC/AC-Adapter

## ■ Interfaces

For VGA : 1x HD Sub-D Jack  
For Power Supply : 1x DC Jack, 115-230 V

## ■ Cabinet

ruggedised Cabinet made of steel and aluminium  
varnished RAL 6031 fine structure  
filter Pane Conturan Standard  
4 Handles

## ■ Dimensions

960 x 610 x 100 mm (W x H x D)

## ■ Poids

60Kg

## ■ Environmental

MIL STD 810F

## ■ Class of protection

IP 54

## ■ Temperature

Operating : -10°C to 50°C  
Storage : -20°C to 60°C



Display 40"



Display 21"

Feel free to contact us for further informations or connect to the website [www.tetracomputer.com](http://www.tetracomputer.com)



Customised mounting systems (In Option) guarantee an high cross sectioned operating spectrum.



Shockmount Unit



Detailed view of shockmount Unit



Stand unit